

## Slide and Turn System



☐ Inquiry ☐ Order

☐ ATENAS System

☐ NIKEA System (PARKING)

☐ NIKEA System (Inline 360°)

Company stamp/address:

Contact person: \_\_\_\_\_

Telephone: \_\_\_\_\_

Quotation No: \_\_\_\_\_

Commission: \_\_\_\_\_

Number of Units: \_\_\_\_\_

Corner angles 90° - 180°: \_\_\_\_\_ pieces

Corner angles 0° - 21°: (Nikea Parking sist.): \_\_\_\_\_ pieces

Opening direction: ☐ inwards folding ☐ outwards folding ☐ 50%-50% , Sist. Nikea (Inline 360°)

Dimensions: Width: \_\_\_\_\_ (Total unfolding) Height: \_\_\_\_\_ (incl. possible floor recession)

Number of Panels: \_\_\_\_\_ to the left \_\_\_\_\_ to the right

Colour: ☐ Aluminium anodized ☐ RAL 9010 ☐ Special Colour: \_\_\_\_\_

Glazing: ☐ 8 mm tempered glass, clear ☐ 10 mm tempered glass, clear ☐ Special glass: \_\_\_\_\_

with Heat-Soak-Test

with Heat-Soak-Test

### Operation/Handle:

☐ Pull rod (Standard)

Double sash lock: ☐ yes ☐ no

☐ Knob

Vertical frame profiles: ☐ yes ☐ no

☐ Latch

Gap gaskets ☐ 1 pc per panel joint

Handle height = \_\_\_\_\_ (indicate handle height from lower panel edge)

Please attach a floor plan resp. a view sketch and remarks! (Advice: Use interior view)

Please fax to 0091-80-22213703